

[Updated Constantly]

HERE

[Introduction to Linux II – Chapter 15 Exam Answers 2019 + PDF file](#)

1. The ____ command used to disable a network interface is identical to ____.
 - ifdown eth0, ifconfig –down eth0
 - ifdown eth0, ip eth0 down
 - ifdown eth0, ifconfig eth0 up
 - **ifdown eth0, ifconfig eth0 down**
2. Which command is used to assign a netmask to *eth1*?
 - ifconfig eth1 submask 255.255.255.224
 - ifconfig eth1 –net-mask 255.255.255.224
 - ifconfig eth1 netmask 255.255.255.*
 - **ifconfig eth1 netmask 255.255.255.224**
3. The *eth0* NIC has been mapped to two IP addresses. This is known as:
 - **IP aliasing**
 - IP replicating
 - IP mapping
 - IP routing
4. Which of the following is not shown in the output of the ifconfig command?
 - Packets received
 - **TTL**
 - Packets transmitted
 - Packets dropped
5. The IP address of your host is **192.168.10.16**. In order to connect to another host with the IP address of **192.86.74.16**, your router will have to be connected to the subnets:
 - 192.168.10.0 and 255.255.255.0
 - 192.168.1.1 and 192.86.74.0
 - **192.168.10.0 and 192.86.74.0**
 - 255.255.255.0 and 192.86.74.0
6. Which file will be used to enable DHCP based configuration on Red Hat based systems?
 - /etc/sysconfig/network-scripts/ifconfig-eth0
 - /etc/network-scripts/ifcfg-eth0
 - **/etc/sysconfig/network-scripts/ifcfg-eth0**

- `/etc/sysconfig/network-scripts/eth0`
7. You ping a host, which is currently not reachable because of some maintenance activity. You now try to add a route via this host since it will be available shortly. What will be the output of `route add` in this scenario?
- **The route will be ignored and an error will be shown**
 - The route will be ignored without any error
 - The route will be added with a warning
 - The route addition will be completed
8. The ____ file is read at boot time on Red Hat based systems to set the host name.
- `/etc/network/sysconfig`
 - `/etc/sys/config`
 - **`/etc/sysconfig/network`**
 - `/etc/sys/network`
9. Which API is used to query address information from the Name Service Switch (NSS) resolver?
- `getaddrent()`
 - **`getaddrinfo()`**
 - `gethostinfo()`
 - `getaddrfields()`
10. How is the DNS configuration file `/etc/resolv.conf` setup?
- By the `ifconfig` utility
 - Default values provided during installation
 - Downloaded from Internet
 - **By network initialization scripts**
11. What type of interface is a network interface card?
- Software interface
 - **Hardware interface**
 - Physical interface
 - Proxy interface
12. Which file contains host and routing details of all configured network interfaces for Red Hat based systems?
- `/etc/sysconfig`
 - `/etc/sys/network`
 - `/etc/network`
 - **`/etc/sysconfig/network`**

13. The view only options of the `ifconfig` command need root privileges.

True or False?

- True
- **False**

14. Which command is used to find the netmask of `eth0` interface?

- **`ifconfig eth0`**
- `ifconfig -A`
- `ifconfig -eth0`
- `ifconfig -netmask eth0`

15. The `ifup` command can read interface definitions from a file other than the default file.

True or False?

- **True**
- False

16. The routing table shows an entry with `genmask 0.0.0.0`, this indicates the _____.

- Default Host
- **Default Route**
- Default Subnet Mask
- Default Name Server

17. Which command is used to setup broadcast addresses for a network interface?

- **`ifconfig`**
- `ifup`
- `route`
- `traceroute`

18. Which file is referred to on systems where DNS is not set up?

- `/etc/host-config`
- `/etc/resolv.conf`
- `/etc/network-hosts`
- **`/etc/hosts`**

19. Which configuration file is referred to for DNS resolution?

- `/etc/dns.conf`
- `/etc/names.conf`
- **`/etc/resolv.conf`**
- `/etc/hosts`

20. The kernel's routing table contains static and dynamic routes.

True or False?

- True

- **False**

21. Which command is used to delete entries from the routing table?

- route --del
- **route del**
- route rm
- route down

22. Which of the information listed below is not shown by the ping command?

- TTL
- **Route to the destination**
- Round-trip Time
- Packet Loss

23. You want to switch the NIC cards of two servers currently in use. Which command will be used to disable the interfaces for this activity?

- **ifdown**
- nicdown
- route down
- ip down

24. The ifdown command can be used to disable all configured network interfaces.
True or False?

- **True**
- False

25. The _____ command is used to view the fully qualified domain name of the host.

- hostname
- cat /etc/hosts
- **hostname -f**
- uname

26. Which of the configuration directives given below is not found in the */etc/resolv.conf* file?

- *domain*
- *sortlist*
- *nameserver*
- ***parameters***

27. Which file is referred to by the Name Service Switch (NSS) resolver?

- */etc/resolv.conf*
- */etc/hosts*
- ***/etc/nsswitch.conf***

- `/etc/nssconfig.conf`

28. The `/etc/nsswitch.conf` file defines the order in which DNS and the `/etc/hosts` file are queried for host name information.

True or False?

- **True**
- False

29. Which command can you use to block packets to a specific host?

- `route reject`
- `route block`
- **`route add with reject option`**
- `route del`